

2

3

4

5

1

2

3

1

2

3

4

1

2

1

2

1. A method for determining Cyclic Redundancy Check (CRC) parity of data, such data comprising a plurality of bytes, each one of the bytes having a parity bit, the plurality of bytes of data having a CRC, comprising:

generating the parity of the parity bits of the plurality of bytes of the data, such generated parity being the parity of the CRC of such data.

- 2. A method for performing a check of the parity bit of a Cyclic Redundancy Cycle (CRC) of data, such data comprising a plurality of bytes, each byte having a parity bit, such method comprising:
 - generating parity of the parity bits of the plurality of data bytes; comparing such generated parity with the parity bit of the CRC of the data.
 - 3. A method for determining Cyclic Redundancy Check (CRC) parity of data, such data having a parity bit, the data having a CRC, comprising:

 comparing the parity of the data with the parity bit of the CRC of the data.
 - 4. A method comprising:
 receiving data having a plurality of N bytes: [D(0), D(1), ..., D(N-1]) each byte
 having a parity bit p;
 computing the parity of [P(0), P(1), ...P(N-1)].
 - 5. A method for computing parity, p, of the Cycle Redundancy Cycle (CRC) of data protected with such (CRC), comprising:
- receiving data having a plurality of N bytes: [D(0), D(1), ...,D(N-1]) each byte

 having a parity bit p;
- computing the parity of [P(0), P(1), ...P(N-1)], such computed parity being equal to the parity p of the CRC.
 - 6. A method for determining a parity, p, error of the Cycle Redundancy Cycle (CRC) of data protected with such (CRC), comprising:

4	having a parity bit P;
5	computing the parity of $[P(0), P(1),P(N-1)]$;
6	comparing the computed parity with the parity p of the CRC, a difference between PP
7	and p indicating an error in p.
1	7. A method for determining a parity error of the Cyclic Redundancy Cycle (CRC)
2	of DATA, such DATA comprising a series of data words terminating in a CRC portion, such

receiving data having a plurality of N bytes [D(0), D(1), ..., D(N-1]) each byte 4 having a parity bit p; 5

computing the parity of [P(0), P(1), ...P(N-1)];

method comprising:

comparing the computed parity with the parity of the CRC, a difference between the computed parity and of the parity of the CRC indicating an error in the parity of the CRC.

receiving data having a plurality of N bytes: [D(0), D(1), ..., D(N-1]) each byte

1

3

3

6

7

8